mBio Terminal MULTI-BIOMETRIC

Logitime



Logitime mBio is a multi-biometric terminal for Time & Attendance and Access Control. The Logitime mBio combines Facial Recognition, Fingerprint and RFID badge technology. The terminal has a 4.3" colour touchscreen, a customisable user interface and is easy, fast and intuitive.

3D face recognition

The mBio has a very high identification speed. Up to 1200 face templates can be stored in identification mode.

The terminal is able to detect whether the face is an actual face or a photo, thus enhancing the security level of verification.

Fingerprint identification

The mBio can store up to 2000 finger templates. Enrollment of multiple fingers per employee is supported. Fingerprint scans are fast and accurate.

Enrollment & distribution

Enrollment of an employee can be done on any mBio terminal. Logitimes smart template distribution system ensures all terminals are updated automatically.

Three-in-one

Employees can make use of any combination of fingerprint, face recogition and/or a badge. This allows employees to use their preferred method of use identification.

Added value

The mBio is more affordable than most single input terminals, and comes with a standard 3 year warranty.

Touchless booking

Using face recognition, bookings can be made without touching the terminal. This is ideal for environments with high hygienic standards and/or access control.

Combine hardware

The mBio can be used side by side with your current hardware. The biometric system works independently of your current hardware. Enabling you to expand on your current system with the best solution for the best price.

HIGHLIGHTS

Face recognition: 1,200 templates (3,000 in verification mode)

Fingerprints: 2,000 templates

RFID support: EM, Mifare, Mifare Desfire

4.3" Touchscreen with colour display

Relay for access control

3 year warranty

Custom interactive Logitime firmware

Scalable solution


The mBio is a scalable solution that can be used in a wide area of applications. It is suitable for both small and very large companies alike.

The mBio is exclusively available at your official Logitime provider.



Display4,3" Touch Screen (10.9 cm)Face Template Capacity1,200 (1:N, Identification) 3,000 (1:1, Verification)Fingerprint Template Capacity2,000ID Card Capacity10,000ID Card TechnologyEM, optional: Mifare, Mifare DesfireIP RatingIP 54Offline Logs Capacity100,000CommunicationTCP/IPPower Supply12V, 3AOptional Functions3G, Wifi, 2000mAh Battery BackupOperating Temperatures0°C - 45°C (32°F - 113°F)Operation Humidity20% - 80%Dimensions (Width x Height x Depth)193.6 x 165 x 111 mm (7.6" x 4.5" x 4.4")	TECHNICAL SPECIFICATIONS	
Frace femipiate Capacity3,000 (1:1, Verification)Fingerprint Template Capacity2,000ID Card Capacity10,000ID Card TechnologyEM, optional: Mifare, Mifare DesfireIP RatingIP 54Offline Logs Capacity100,000CommunicationTCP/IPPower Supply12V, 3AOptional Functions3G, Wifi, 2000mAh Battery BackupOperating Temperatures0°C - 45°C (32°F - 113°F)Operation Humidity20% - 80%	Display	4,3" Touch Screen (10.9 cm)
ID Card Capacity 10,000 ID Card Technology EM, optional: Mifare, Mifare Desfire IP Rating IP 54 Offline Logs Capacity 100,000 Communication TCP/IP Power Supply 12V, 3A Optional Functions SG, Wifi, 2000mAh Battery Backup Operating Temperatures 0°C - 45°C (32°F - 113°F)	Face Template Capacity	
ID Card Technology EM, optional: Mifare Desfire IP Rating IP 54 Offline Logs Capacity 100,000 Communication TCP/IP Power Supply 12V, 3A Optional Functions SG, Wifi, 2000mAh Battery Backup Operating Temperatures 0°C - 45°C (32°F - 113°F)	Fingerprint Template Capacity	2,000
IP Rating IP 54 Offline Logs Capacity 100,000 Communication TCP/IP Power Supply 12V, 3A Optional Functions 3G, Wifi, 2000mAh Battery Backup Operating Temperatures 0°C - 45°C (32°F - 113°F) Operation Humidity 20% - 80%	ID Card Capacity	10,000
Offline Logs Capacity 100,000 Communication TCP/IP Power Supply 12V, 3A Optional Functions 3G, Wifi, 2000mAh Battery Backup Operating Temperatures 0°C - 45°C (32°F - 113°F) Operation Humidity 20% - 80%	ID Card Technology	EM, optional: Mifare, Mifare Desfire
Communication TCP/IP Power Supply 12V, 3A Optional Functions 3G, Wifi, 2000mAh Battery Backup Operating Temperatures 0°C - 45°C (32°F - 113°F) Operation Humidity 20% - 80%	IP Rating	IP 54
Power Supply 12V, 3A Optional Functions 3G, Wifi, 2000mAh Battery Backup Operating Temperatures 0°C - 45°C (32°F - 113°F) Operation Humidity 20% - 80%	Offline Logs Capacity	100,000
Optional Functions 3G, Wifi, 2000mAh Battery Backup Operating Temperatures 0°C - 45°C (32°F - 113°F) Operation Humidity 20% - 80%	Communication	TCP/IP
Operating Temperatures 0°C - 45°C (32°F - 113°F) Operation Humidity 20% - 80%	Power Supply	12V, 3A
Operation Humidity 20% - 80%	Optional Functions	3G, Wifi, 2000mAh Battery Backup
	Operating Temperatures	0°C - 45°C (32°F - 113°F)
Dimensions (Width x Height x Depth) 193.6 x 165 x 111 mm (7.6" x 6.5" x 4.4")	Operation Humidity	20% - 80%
	Dimensions (Width x Height x Depth)	193.6 x 165 x 111 mm (7.6" x 6.5" x 4.4")
Package Weight 1.87 kg (4.12 lbs)	Package Weight	1.87 kg (4.12 lbs)


INCLUDED IN THE BOX



mBio Terminal




Back Plate



Power Adapter



Access Control Interface Cable



Mounting Paper



Screws and Plugs

Screwdriver



Paper Ruler